



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Patent Application of:
PIDCOCK et al.

Serial No.: 10/714,600
Filed: 11/18/03

Group: 3746
Examiner: CASAREGOLA, Louis J.

Title: SEALING ARRANGEMENT

PRIORITY CLAIM SUBMISSION AND CERTIFIED COPY

Date: September 8, 2005

Hon. Commissioner of Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:


It is respectfully requested that under the provisions of 35 USC 119/365, this application be given the benefit of the foreign filing date of the following, a certified copy of which is attached hereto:

Application No.
0227842.2

Country of Origin
Great Britain

Filed
11/29/02

Respectfully submitted,


W. Warren Taltavull
Reg. No. 25647

MANELLI DENISON & SELTER PLLC
2000 M Street N.W. Suite 700
Washington D.C. 20036
202 261 1047

THIS PAGE BLANK (USPTO)



USA

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

CERTIFIED COPY OF
PRIORITY DOCUMENT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation and Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein together with the statement of inventorship and of right to grant of a Patent (Form 7/77), which was subsequently filed.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1985 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name in which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed *A. B. Jones*

Dated 9 October 2003

An Executive Agency of the Department of Trade and Industry

THIS PAGE BLANK (USPTO)



29NOV02 E767291-1 D00370
P01/7700 0.00-0227842.2

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

THE PATENT OFFICE
B

29 NOV 2002

NEWPORT

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

DY3051

2. Patent application number

(The Patent Office will fill in this part)

0227842.2

3. Full name, address and postcode of the or of each applicant (underline all surnames)

ROLLS-ROYCE PLC
65 BUCKINGHAM GATE
LONDON
SW1E 6AT

ROLLS-ROYCE
DEUTSCHLAND
LTD & CO KG
ESCHENWEG 11
15827 DAHLEWITZ

Patents ADP number (if you know it)

8504375001

If the applicant is a corporate body, give the country/state of its incorporation

ENGLAND

GERMANY

8372112002

4. Title of the invention

SEALING ARRANGEMENT

5. Name of your agent (if you have one)

M A GUNN

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

ROLLS-ROYCE plc
PATENTS DEPARTMENT
PO BOX 31
DERBY
DE24 8BJ

Patents ADP number (if you know it)

3962001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

YES

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description

8

Claim(s)

3

Abstract

1

Drawing(s)

5

TS

[Signature]

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

4

/

Request for preliminary examination and search (Patents Form 9/77)

1

/

Request for substantive examination (Patents Form 10/77)

1

/

Any other documents (please specify)

DEPOSIT ACCOUNT FEE SHEET

[Signature]

11.

I/We request the grant of a patent on the basis of this application.

Signature

[Signature]

Date

M A GUNN

28.11.2002

12. Name and daytime telephone number of person to contact in the United Kingdom

K A WHITE


01332 249452

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.



Statement of inventorship and of right to grant of a patent

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

DY3051

2. Patent application number

(if you know it)

0227842.2

3. Full name of the or of each applicant

ROLLS-ROYCE PLC AND ROLLS-ROYCE DEUTSCHLAND LTD & CO KG

4. Title of the invention

SEALING ARRANGEMENT

5. State how the applicant(s) derived the right from the inventor(s) to be granted a patent

BY VIRTUE OF SECTION 39(1) (a) OF THE PATENTS ACT 1977

6. How many, if any, additional Patents Forms 7/77 are attached to this form?

3

(see note (c))

7.

I/We believe that the person(s) named over the page (and on any extra copies of this form) is/are the inventor(s) of the invention which the above patent application relates to.

Signature

Date

M A GUNN

28.11.2002

8. Name and daytime telephone number of person to contact in the United Kingdom

K A WHITE

01332 249452

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

ANTHONY PIDCOCK
70 SUTTON AVENUE
CHELLASTON
DERBY
DE731PH

Patents ADP number (if you know it):

7844715001

MIKLOS GERENDAS
EICHHORNSTRASSE 25
15806 ZOSSEN
GERMANY

Patents ADP number (if you know it):

8516346001

VOLKER HERZOG
KARL-MARX-STRASSE 105
15745 WILDAU
GERMANY

Patents ADP number (if you know it):

8516361001

Reminder

Have you signed the form?

Sealing Arrangement

This invention relates to sealing arrangements for combustors. More particularly, but not exclusively, the invention relates to sealing arrangements for combustors in gas turbine engines.

In order to ignite the fuel in the combustion chamber of a gas turbine engine, an ignitor plug is arranged to extend into the chamber. The plug extends through a hole in the combustor casing. During operation of the engine, the combustor casing moves relative to the combustion chamber, because of the different thermal expansions. The ignitor hole needs to be larger than the ignitor plug to compensate for this movement.

A seal is used to overcome the problem of leakage through the hole. The seal is mounted in a tower arrangement extending radially outwardly from the combustor. A ring welded on to the top of the tower secures the seal to the tower.

According to one aspect of the invention there is provided a seal arrangement for a combustor, the seal arrangement comprising a seal defining a first aperture, an inner combustor wall defining a second aperture, and an outer combustor wall defining a third aperture, the first, second and third apertures being arranged in line with each other to receive an article therethrough, wherein the seal is arranged between the inner and outer combustor walls.

Desirably, the seal is secured between the inner and outer walls, and may engage at least one of the inner and outer walls. Desirably, the seal engages both of said inner and outer walls. Preferably, the seal is secured between said walls by the inner and outer walls.

The seal may comprise an outwardly extending portion to engage the, or each, combustor wall. Preferably, the outwardly extending portion extends radially outwardly.

The seal member may further include holding means to hold the article. Preferably, the holding means comprises guide member to guide the article into said aperture. The holding means may extend through the aperture in the outer combustor wall. The holding means is preferably conical in configuration.

Preferably, the inner wall comprises a wall member which may comprise a tile. The inner wall may be formed of a plurality of said wall members.

10 The wall member may comprise a main portion and spacer to space the main portion from the outer wall. Preferably, the spacer extends around the second aperture. The spacer may be annular in configuration. The inner wall may define cooling means around the second aperture. The cooling
15 means may comprise a plurality of cooling channels. The channels may comprise a plurality of cooling holes extending through the inner wall. Alternatively, or in addition, the cooling means may comprise a plurality of cooling grooves extending along an outer surface of the
20 inner wall, desirably, extending to the aperture in the inner wall.

Preferably, at least some of the cooling channels extend inwardly. At least some of the cooling channels may extend at an acute angle to the aperture. Preferably,
25 where the second aperture is generally circular, at least some of the cooling channels are tangential to the second aperture or may have a tangential component to the second aperture.

The cooling channels may be arranged in an array of
30 channels extending around the second aperture. The array of channels is preferably an annular array. Conveniently, the array comprises a plurality of rows of cooling channels, one of said rows preferably comprising a plurality of cooling grooves which may extend along the
35 inner wall. Preferably, the grooves extend to the aperture in said inner wall.

Preferably the plurality of rows of cooling channels comprises a plurality of rows of cooling holes which may extend through the inner wall.

Preferably, the cooling means can receive a cooling fluid from a region between the inner and outer walls.

An embodiment of the invention will now be described by way of example only, with reference to the accompanying drawings, in which:-

Fig. 1 is a sectional side view of the upper half of a gas turbine engine;

Fig. 2 is a sectional side view of a combustor for use in the gas turbine engine shown in Fig. 1;

Fig. 3 is a sectional side view of the region of the combustor marked III shown in Fig. 2;

Figs. 4A and 4B are top plan views of an inner wall tile of Fig. 3, showing cooling holes; and

Figs. 5A and 5B are top plan views of the wall tiles shown in Fig. 3, indicating the cooling grooves.

With reference to Fig. 1, a ducted fan gas turbine engine generally indicated at 10 has a principal axis X-X. The engine 10 comprises, in axial flow series, an air intake 11, a propulsive fan 12, a compressor region 113 comprising an intermediate pressure compressor 13, and a high pressure compressor 14, a combustion arrangement 115 comprising a combustor 15, and a turbine region 116 comprising a high pressure turbine 16, an intermediate pressure turbine 17, and a low pressure turbine 18. An exhaust nozzle 19 is provided at the tail of the engine 10.

The gas turbine engine 10 works in the conventional manner so that air entering the intake 11 is accelerated by the fan to produce two air flows: a first air flow into the intermediate pressure compressor 13 and a second air flow which provides propulsive thrust. The intermediate pressure compressor 13 compresses the air flow directed into it before delivering the air to the high pressure compressor 14 where further compression takes place.

The compressed air exhausted from the high pressure compressor 14 is directed into the combustor 15 where it is mixed with fuel and the mixture combusted. The resultant hot combustion products then expand through, and thereby drive the high, intermediate and low pressure turbine 16, 17 and 18 before being exhausted through the nozzle 19 to provide additional propulsive thrust. The high, intermediate and low pressure turbines 16, 17 and 18 respectively drive the high and intermediate pressure compressors 14 and 13 and the fan 12 by suitable interconnecting shafts 118.

Referring to Fig. 2, the combustion arrangement 115 comprises the combustor 15, an outer annular casing 20, and an inner annular casing 22. The combustor 15 comprises an outer annular wall arrangement 24 and an inner annular wall arrangement 26. A combustion chamber 27 is defined between the inner and outer wall arrangements 24, 26.

The outer annular wall arrangement 24 comprises a first annular inner wall 28 and a first annular outer wall 30. Similarly, the inner annular wall arrangement 26 comprises a second annular inner wall 32 and a second annular outer wall 34. The combustor means 15 also includes an inlet arrangement 36 through which compressed gas from the compressor region 113 can pass via a compressor vane 37 to enter the combustor 15. The combustion assembly 115 also includes fuel injection means 38 for injecting fuel into the combustion chamber 27 via a heat shield 40. The heat shield 40 is mounted upon a base plate 42 and a cowl 44 extends over the base plate 42.

An outlet assembly 46 is provided for the combusted gases to pass to the turbine region 116 via a turbine vane 47.

In order to ignite the fuel in the combustor chamber 27 at the start up of the engine 10, there is provided an ignitor plug 50 which extends from a region outside the outer casing 20 to the combustion chamber 27. In order to

prevent leakage of gases from the combustion chamber 27 around the ignitor plug 27, a seal 52 is provided in the outer wall arrangement 24.

The first inner annular wall 28 is formed of a plurality of tiles 43. Some of the tile 43 are constructed to allow an ignitor plug 50 to extend therethrough into the combustion chamber 27, as will be explained below. These tiles are designated 43A. The second inner annular wall 32 is also formed of a plurality of tiles 43.

Reference is now made to Fig. 3, which shows the region marked III in Fig. 2., which shows the tile 43A and the seal 52 in more detail.

The seal 52 comprises a radially outwardly extending portion in the form of a flange member 60 which defines a first aperture 62 for the ignitor plug 50. The seal 52 also includes a conical guide member 64 extending outwardly from the flange member 60 from the edge region of the aperture 62.

The tile 43A defines a second aperture 66. The first, second and third apertures 62, 64, 66 are arranged in line with each other so that an inner end region 50A of the ignitor plug 50 can extend into the combustion chamber 27.

The first outer wall 30 of the outer wall arrangement 24 defines a third aperture 68 through which the conical guide member 64 extends.

Thus, as can be seen from Fig. 3, the seal 52 is secured to the combustor 15 by being arranged such that the flange portion 60 is disposed between the first outer wall 30 and the tile 43A.

The tile 43A includes a main portion 70 and an annular spacer 72 extending around the first aperture 62 to space the main portion 70 from the outer wall 30. The main portion 70 has a radially outer surface 74 facing the first outer wall 30. The region of the outer surface 74 in contact with the seal 52 can be planar or curved.

As can be seen, the flange 60 of the seal 52 engages

the tile 43A on its radially outer surface 74. If desired, the flange 60 of the seal member 52 could engage the radially inner surface 76 of the outer wall 30. The first outer wall 30 has a radially inner surface 76 facing the first inner wall 28.

The tile 43A is provided with cooling means in the form of a plurality of cooling channels 80. In the embodiment shown, there are two types of cooling channels, namely cooling holes 82 which extend through the body of the main portion 70, as shown, and cooling grooves 84 which extend along the outer annular surface 74 of the main portion 70. The cooling channels 80 are provided to cool the region of the surface 74 of the main portion 70 of the tile 43A that is engaged by the flange member 60 of the seal 52. An annular groove 86 extends around the first aperture 62 inwardly of the spacer 72.

The seal 52 can also be provided with cooling channels 80X. The surface of the seal 52 in contact with the outer surface 74 of the inner wall 28 may define additional cooling grooves 84X. Also, additional cooling holes 82X may extend through the flange member 60 of the seal 52.

Referring to Figs. 4A and 4B, there is shown a top plan view of the tile 43A which shows the annular groove 86 arranged radially inwardly of the spacer member 72, and the cooling holes 82 extending radially inwardly from the annular grooves 86. The cooling grooves 84 have been omitted for the sake of clarity.

The arrows A shown in Fig. 4A are intended to represent a first row of the cooling holes 82. As can be seen from Fig. 4A, the first row A of cooling holes 82 direct cooling air radially inwardly towards the second aperture 66. Fig. 4B shows a further set of arrows which represent another annular row B of cooling holes 82, which direct cooling air towards the second aperture 68, but the orientation of the cooling holes 82 forming the second row B has a tangential component thereto. Fig. 4B shows

cooling holes 82 having a tangential component providing a constant swirl. In other embodiments, the swirl can change along the circumference. For example, the cooling holes 82 shown in Fig. 4B and represented by the arrows B can be arranged in two distinct groups, each group having an opposing sense of rotation.

Each of the rows of cooling holes 82 which are represented by the arrows A and B in Figs. 4A and 4B are provided with air from the annular groove 86. The cooling holes 82 represented by the arrows A may be at a first level within the main portion 70 of the tile 43A, and the cooling holes 82 represented by the arrows B may be at a second level within the main portion 70 of the tile 43A. It will be appreciated by those skilled in the art that the precise orientations of cooling holes 82 will depend upon the conditions inside and outside the combustion chamber 27.

Referring to Figs. 5A and 5B, there are again shown top plan views of the tile 43A shown in Fig. 3, in which the cooling grooves 84 are shown. The cooling holes 82 are omitted for clarity. The cooling grooves 84 direct air along the surface 74 of the main portion 70 of the tile 43A. The cooling fluid directed through the cooling grooves 84 to be divided from the annular groove 86. The arrows C in Fig. 5A shows the direction of air flowing through the radially inwardly directed cooling grooves 84. The arrows D in Fig. 5B shows that air is directed with a tangential component relative to the second aperture 66. Fig. 5B shows cooling grooves 84 having a tangential component providing a constant swirl. In other embodiments, the swirl can change along the circumference. For example, the cooling grooves 84 shown in Fig. 5B, and having a flow of air represented by the arrows D, can be arranged in two distinct groups, each group having an opposing sense of rotation. The purpose of the cooling grooves 84 is to provide further cooling in the event that

cooling fluids supplied by the cooling holes 82 is not sufficient and may provide cooling for the main portion 60 of the seal 52.

Referring back to Fig. 3 there is shown four rows of
5 cooling holes 82A, 82B, 82C and 82D where each row is radially further outwardly to the previous row. In such a case, the innermost row is provided with a mainly radially inward orientation, and the orientation of each subsequent row outwardly therefrom is provided with an increased
10 tangential component.

There is thus described a seal arrangement 52 for holding an ignitor plug 50 in a combustion chamber 27 of a gas turbine engine. The preferred embodiment has the advantage over prior art arrangements which feature tower
15 members are reduced weight, parts count and cost.

Various modifications can be made without departing from the scope of the invention, for example the arrangement of cooling holes and cooling channels can be altered. Also, the above arrangement could be used for
20 other articles to be inserted into the combustion chamber, for example a Helmholtz resonator.

Whilst endeavouring in the foregoing specification to draw attention to those features of the invention believed to be of particular importance it should be understood that
25 the Applicant claims protection in respect of any patentable feature or combination of features hereinbefore referred to and/or shown in the drawings whether or not particular emphasis has been placed thereon.

Claims:-

1. A seal arrangement for a combustor, the seal arrangement comprising a seal defining a first aperture, an
5 inner combustor wall defining a second aperture, and an outer combustor wall defining a third aperture, the first, second and third apertures being arranged in line with each other to receive an article therethrough, wherein the seal is arranged between the inner and outer combustor walls.
- 10 2. A seal arrangement according to claim 1, wherein the seal is secured between the inner and outer walls.
3. A seal arrangement according to claim 1 or 2, wherein the seal engages at least one of the inner and outer walls.
4. A seal arrangement according to any preceding claim,
15 wherein the seal engages both of the inner and outer walls and is secured between said walls by said inner and outer walls.
5. A seal arrangement according to any preceding claim wherein the seal comprises an outwardly extending portion
20 to engage the, or each, combustor wall.
6. A seal arrangement according to claim 5, wherein the outwardly extending portion extends radially outwardly.
7. A seal arrangement according to any preceding claim wherein holding means to hold the article, the holding
25 means extending through the aperture in the outer combustor walls.
8. A seal arrangement according to claim 7, wherein the holding means comprises a guide member to guide the article into said apertures.
- 30 9. A seal arrangement according to claim 7 or 8, wherein the holding means is conical in configuration.
10. A seal arrangement according to any preceding claim wherein the inner wall comprises a plurality of wall members.
- 35 11. A seal arrangement according to claim 10, wherein the wall member comprises a main portion and a spacer to space

the main portion from the outer wall, the spacer extending around the second aperture.

12. A seal arrangement according to any preceding claim, wherein the inner wall defines cooling means around the
5 second aperture.

13. A seal arrangement according to claim 11, wherein the cooling means comprises a plurality of cooling channels and a cooling fluid supply groove extending around the second aperture, wherein the cooling channels extend from the
10 supply groove.

14. A seal arrangement according to claim 13, wherein the cooling channels comprise a plurality of holes extending through the inner wall.

15. A seal arrangement according to claim 13 or 14,
15 wherein the cooling channels comprise a plurality of grooves extending along an outer surface of the inner wall to said second aperture therein.

16. A seal arrangement according to any of claims 12 to 15, wherein at least some of the cooling channels extend
20 inwardly towards the second aperture.

17. A cooling arrangement according to any of claims 12 to 16 wherein at least some of the cooling channels extend at an acute angle to the second aperture.

18. A seal arrangement according to any of claims 12 to
25 17, wherein where the second aperture is generally circular in configuration, at least some of the cooling channels are tangential to the second aperture, or have a constant or variable tangential component thereto.

19. A seal arrangement according to any of claims 12 to
30 18, wherein the cooling channels are arranged to provide an array of channels extending around the second aperture.

20. A sealing arrangement according to claim 19, wherein the array of channels is an annular array and comprises a plurality of rows of cooling channels.

35 21. A sealing arrangement according to claim 20, wherein one of said rows comprises a plurality of cooling grooves

extending along the inner wall.

22. A sealing arrangement according to claim 20 or 21, wherein the plurality of rows of cooling channels comprises a plurality of rows of cooling holes extending through the
5 inner wall.

23. A sealing arrangement according to any preceding claim wherein the seal defines seal cooling means around the first aperture.

24. A sealing arrangement according to claim 23, wherein
10 the seal cooling means comprises a plurality of seal cooling holes extending through an outwardly extending portion of the seal.

25. A sealing arrangement according to claim 24, wherein the seal cooling means comprises a plurality of seal
15 cooling grooves in the outwardly extending portion, extending along a surface of the seal in contact with the inner wall.

26. A combustion arrangement comprising a combustor having inner and outer walls, wherein at least one of said walls
20 comprises a sealing arrangement as claimed in any preceding claim.

27. A gas turbine engine incorporating a combustion arrangement as claimed in claim 21.

28. A sealing arrangement substantially as herein
25 described with reference to Figs. 3, 4A, 4B, 5A and 5B.

29. A combustion means substantially as herein described with reference to Fig. 2.

30. Any novel subject matter or combination including novel subject matter disclosed herein, whether or not
30 within the scope of or relating to the same invention as any of the preceding claims.

AbstractSeal Arrangement (Fig. 3)

5

A seal arrangement for a combustor (15) is disclosed. The seal arrangement comprises a seal (52) defining a first aperture (62), an inner combustor wall (28) defining a second aperture (66), and an outer combustor wall (30) defining a third aperture (68). The first and second apertures (66, 68) are arranged in line with each other to receive an article (50) therethrough. The seal (52) is arranged between the inner and outer combustor walls.

10





FIG. 1

THIS PAGE BLANK (USPTO)



THIS PAGE BLANK (USPTO)






Fig 3

THIS PAGE BLANK (USPTO)



THIS PAGE BLANK (USPTO)




Fig 5A




Fig 5B

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)